

## DRY RELEASE

### PTFE DRY LUBRICANT & RELEASE AGENT

**TB-81000000-00**



#### DESCRIPTION

**DRY RELEASE** is the ultimate non-staining, colorless, and oil-free dry lubricant. Its low-odor formula outperforms silicone and graphite, providing superior lubrication without the mess. Ideal for die casts, injection molds, gears, hinges, pulleys, and more. It reduces friction and extends equipment life. With an ultra-fine PTFE powder, **DRY RELEASE** works across temperatures from -100°F to 500°F and contains no hexane, making it a safer, cleaner choice. Experience the cleaner, unrivaled solution to lubrication—no mess, no hassle, just results. Experience the game-changing power of **DRY RELEASE** today!

#### DIRECTIONS

Shake can for 1 full minute to thoroughly agitate. Apply to clean, dry surface. Hold can 5-10 inches from surface and apply evenly. Thin coats are preferable.

#### FEATURES & BENEFITS

- Colorless, Stainless, Low Odor
- Oil-Free
- Paintable
- Prolongs Tool Life
- Reduces Friction
- Stops Sticking

#### RECOMMENDED USES

- Die casts and injection molds
- Gears and pulleys
- Conveyor systems
- Hinges and locks
- Tools and machinery
- Paintable surfaces
- Non-staining environments

PROPERTIES	
Color	White
Fragrance	Petroleum odor
Spray Pattern	Mist
Flash Point	Not determined
Dielectric Strength	Not determined
VOC Content	98.8%
Propellant	Yes
PACKAGING	
Can Size	16 oz
Net Weight	10 oz
Extender Tube	No
Packaged	12 cans per case
Shipping Weight	11 lbs
REGULATORY	
Ozone Depleting Compounds	None
VOC Compliant	Not determined
Recyclable Packaging	Yes

For industrial use only. Refer to the product's Safety Data Sheet (SDS) for complete safety, handling, and first aid information.