



PENETRATING GEL LUBRICANT

TB-94700000-00



DESCRIPTION
PENETRATING GEL LUBRICANT locks onto metal surfaces with an ultra-adhesive gel and forms a resilient, pressure-resistant barrier built to endure heat, force, and relentless movement. Engineered with a high-performance blend of synthetic and natural oils plus PTFE, **PENETRATING GEL LUBRICANT** shields components from friction, moisture, and corrosion. Grips where others fail—ideal for hinges, cables, pulleys, chains, and other critical parts exposed to harsh conditions. Delivers lasting protection and keeps systems running smooth, strong, and reliable.

DIRECTIONS

Application directions are not specified.

FEATURES & BENEFITS

- Contains PTFE
- Spray Anywhere 360° Valve
- Handles intense pressure in temperatures ranging from -30°F to 600°F.
- Ultra-adhesive gel formula
- Blend of synthetic & natural oils + PTFE

RECOMMENDED USES

- Chains & cables
- Pulleys & gears
- Hinges & joints
- Exposed machinery
- High-temperature systems

PROPERTIES

| | |
|---------------------|----------------|
| Color | Clear |
| Fragrance | Not determined |
| Spray Pattern | Gel |
| Flash Point | -17°C |
| Dielectric Strength | Not determined |
| VOC Content | Not determined |
| Propellant | Yes |

PACKAGING

| | |
|-----------------|------------------|
| Can Size | 20 oz |
| Net Weight | 13 oz |
| Extender Tube | No |
| Packaged | 12 cans per case |
| Shipping Weight | Not determined |

REGULATORY

| | |
|---------------------------|----------------|
| Ozone Depleting Compounds | None |
| VOC Compliant | Not determined |
| Recyclable Packaging | Yes |

For industrial use only. Refer to the product's Safety Data Sheet (SDS) for complete safety, handling, and first aid information.

Phone: 800-592-5080

Email:terandbrand@chem-masterstl.com

CHEM-MASTER ACQUISITIONS, LLC

3670 Scarlet Oak Blvd.
St. Louis, MO 63122