



# RTV SILICONE CAULK & SEALANT ALUMINUM

TB-51120000-00



## DESCRIPTION

**RTV SILICONE CAULK & SEALANT** is ideal for use wherever a strong, permanent elastic weatherproof adhesive, sealant, or caulk is needed. This product has excellent adhesion characteristics, high chemical resistance, and will not sag or shrink due to severe temperature extremes. Use for sealing cracks in machinery, heating and ventilating duct work, plumbing fixtures, electrical connections, low pressure water and drain pipes. Bonds nameplates, machinery flanges, glass, signs, and electrical insulation, etc. Ideal for caulking windows, doors, walls, ceiling cracks and crevices. Forms in place gaskets. Paint will not adhere to cured material. Meets ASTM C920.

## DIRECTIONS

Surface should be clean and dry and free of oil, tar, dirt and dust for best adhesion. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to the mating surfaces. Starts to cure immediately, fully cures in 24 hours and reaches optimum strength in 7 days.

Leave a small bead of material which will form a sealing "plug" for reuses. To use, gently pull "plug" and begin to use material. If plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

## FEATURES & BENEFITS

- Seals, bonds, and insulates
- Flexible. Easy to use; water and weatherproof
- 100% RTV silicone – industrial strength
- Flexible from -60°F to +400°F
- Caulks tubs, sinks, showers, and plumbing fixtures
- Seals around windows, doors, tile, and marble

## RECOMMENDED USES

- Industrial Facilities
- HVAC Systems
- Plumbing Installations
- Electrical Worksites
- Residential Construction
- Commercial Buildings

## PROPERTIES

|                     |                             |
|---------------------|-----------------------------|
| Color               | Gray                        |
| Fragrance           | Acetic Acid                 |
| Spray Pattern       | Not determined              |
| Flash Point         | Closed cup: >100°C (>212°F) |
| Dielectric Strength | Not determined              |
| VOC Content         | Not determined              |
| Propellant          | Yes                         |

## PACKAGING

|                 |                 |
|-----------------|-----------------|
| Can Size        | 8 oz            |
| Net Weight      | 8 oz (227 g)    |
| Extender Tube   | No              |
| Packaged        | 6 cans per case |
| Shipping Weight | 4.25 lbs        |

## REGULATORY

|                           |                |
|---------------------------|----------------|
| Ozone Depleting Compounds | None           |
| VOC Compliant             | Not determined |
| Recyclable Packaging      | Yes            |

For industrial use only. Refer to the product's Safety Data Sheet (SDS) for complete safety, handling, and first aid information.

Phone: 800-592-5080

Email:terandbrand@chem-masterstl.com

**CHEM-MASTER ACQUISITIONS, LLC**

3670 Scarlet Oak Blvd.  
St. Louis, MO 63122