

## RTV SILICONE GASKET MAKER HIGH TEMP RED

**TB-51170000-00**



**RTV SILICONE GASKET MAKER** adheres to metal, glass, porcelain, ceramics, wood, rubber, and most paints and plastics. It replaces cork, paper, asbestos, felt, and metal gaskets. Offers excellent adhesion, high chemical resistance, and withstands temperatures up to 500°F and pressures up to 330 psi. Virtually unaffected by chemical deterioration, extreme weather, temperature, or aging.

### DESCRIPTION

Surface must be clean, dry, and free of oil, tar, dirt, and dust for best adhesion. Hold can at 45° angle and apply a continuous bead of 1/16" to 1/8" to mating surfaces, encircling all bolt holes. For adhesion to both parts, assemble immediately. For one-part adhesion, allow 10-15 minutes for bead to skin. Assemble parts without over-tightening bolts to avoid squeezing out the gasket. Starts to cure immediately. Fully cures in 24 hours and reaches optimum strength in 7 days. For food applications, wash part after sealant is completely cured. Excess cured material can be trimmed with a sharp blade. Avoid undercutting the seal.

### DIRECTIONS

#### FEATURES & BENEFITS

- Seals, bonds, and insulates
- Low Volatile • Flexible • Easy to use
- Economical • Eliminates waste
- Waterproof & weatherproof
- Eliminates squeeze tubes and cartridge guns
- 100% low volatile RTV silicone
- Meets G.M. and O.E.M. specifications

#### RECOMMENDED USES

- Automotive workshops and garages
- Industrial facilities
- Electrical maintenance areas
- Mechanical repair shops
- Field service environments
- Food processing equipment zones
- Outdoor equipment stations

#### PROPERTIES

Color	Red
Fragrance	Acetic Acid
Spray Pattern	Not determined
Flash Point	Closed cup: >100°C (>212°F)
Dielectric Strength	Not determined
VOC Content	Not determined
Propellant	Yes

#### PACKAGING

Can Size	8 oz
Net Weight	8 oz (227 g)
Extender Tube	No
Packaged	6 cans per case
Shipping Weight	4.25 lbs

#### REGULATORY

Ozone Depleting Compounds	None
VOC Compliant	Not determined
Recyclable Packaging	Yes

For industrial use only. Refer to the product's Safety Data Sheet (SDS) for complete safety, handling, and first aid information.